FT3 PICKUP





WE'LL GET YOU THERE



101, rue de la Production Cowansville, Quebec, Canada J2K 5H5 579.319.0060 | sales@zealmotor.com

WWW.FATTRUCK.COM

FT3 PICKUP



SPECIFICATIONS

| 3000 lb (1357 kg) |
|----------------------|
| 2200 lb (998 kg) |
| 8 (2 front + 6 rear) |
| 25 mph (40 km/h) |
| 3.1 mph (5 km/h) |
| 35°/70% |
| 22°/ 40% |
| 0° |
| 6500 lb (2941 kg) |
| |

| Ground pressure fully loaded |
|------------------------------|
| SAFETY FEATURES |

| ROPS | ISO 3471 |
|--------|------------------------|
| EPA | Stage V |
| Brakes | Automatic safety brake |

 $1.6 \, \text{lb/po}^2 \, (0.11 \, \text{kg/cm}^2)$

DIMENSIONS


| Height with roof rack | 103 in (2620 mm) |
|------------------------------|--------------------|
| Height with air conditioning | 111.4 in (2830 mm) |
| Length | 147 in (3730 mm) |
| Width | 100 in (2540 mm) |
| Ground clearance | 25.5 in (650 mm) |

CONTROLS

| Controller | Microprocessor |
|------------|----------------|
| Steering | Joystick |
| Display | Color display |

WARRANTY

Limited 1 year / 1000 hours (Which ever comes first)



ENGINE

| Make | HATZ |
|---------------------|--------------------------------|
| Model | 4H50TICD |
| Emission standards | EPA Tier 4 Final EU Stage V |
| Number of cylinders | 4 cylinders |
| Displacement | 1.95 L |
| Horsepower | 74 hp (55 kW) |
| Torque @ 1400 RPM | 177 lb-ft (240 N-m |
| Cooling System | Liquid cooled |

ELECTRICAL

| Voltage | 12 V |
|---------------------|---------|
| Alternator capacity | 370 A |
| Battery capacity | 960 CCA |
| Battery type | AGM |

TRANSMISSION

| Туре | Hydrostatic |
|-------------|--------------------|
| Final drive | 4 Hydraulic motors |

BRAKES

| Brakes | Positive deceleration |
|----------------|-----------------------|
| | through hydrostation |
| | transmission |
| Parking brakes | Brake disc applied |
| | nressure released |

TIRES

| Front & Rear | FAT TRUCK® LGP 68 x 24 x 24 in |
|------------------|-----------------------------------|
| Pressure | 0.5 to 4.5 PSI (0.07 to 0.31 BAR) |
| Pressure control | Automatic pressure control |

FUEL SYSTEM

| Capacity | 22 US Gal (83 L |
|-----------------------|-----------------|
| Average fuel autonomy | 12 h |

STANDARD EQUIPMENT

| Standard color: Red or white |
|--|
| Lockable door |
| 2 front seats with 3-points seat belts |

2 openable side windows

Ventilation Fan

Lights: Front, brakes, position, flashers, dome

4 corner LED beacon amber lights

Backup alarm Front mirrors

Front and rear bumpers with hitch

Front and rear ladder with grab handles

Front roof rack Electric horn

Inclinometer with alarm

Backup camera or 4-way backup camera

Master cut-off switch

Cup holders

2 x 12 V charging ports

Lockable fuel cap

D rings Bilge pump Wheel Pods™

Fire extinguisher 2.5 lb ABC

First aid kit

Operator & Maintenance manual

| ront & Rear | FAT TRUCK® LGP 68 x 24 x 24 in |
|-------------------|-----------------------------------|
| Pressure | 0.5 to 4.5 PSI (0.07 to 0.31 BAR) |
| Dunnanuma nambual | Automotic procesure control |

OPTIONS

Custom color Front LED light bar Rear LED light bar

Side working LED lights front and rear

Search light Air conditioning Front feet heater

Fuel heater for engine water and transmission oil

110 V heater cold engine water

and transmission oil

Rear seats with 2 pts safety belts Rear seats with 3 pts safety belts

4-forward facing seats Rear rack with side ladder

Additional battery Front and/or rear winch Rear capstan winch

Studs for ice

Hot sticks storage tubes

Ladder rack Storage box Pintle hook Radio Bluetooth®



